

# PERCEUSE D'ÉTABLI DRILL PRESS

## 550 W













111207  
DPB 25E

550 W

### PERCEUSE D'ÉTABLI - DRILL PRESS TALADROS DE SOBREMESA - ENGENHOS DE FURAR DE COLUNA

DPB 25E

Gencode 3431541112070

	<b>Puissance du moteur</b> Motor power Potencia del motor Potência de motor	550 W (Alu) 230V ~ 50Hz
	<b>Vitesses</b> Speeds Velocidades por correas Velocidades	x16 180 - 2770 min <sup>-1</sup>
	<b>Mandrin autoserrant</b> Keyless chuck Porta brocas automático Buchas de aperto rápido	ø 1-16 mm
<b>A</b>	Type de broche Spindle Cono morse Tipo de encaixe	CM2 MT2
<b>B</b>	<b>Course de la broche</b> Spindle travel Recorrido husillo Curso do encaixe	85 mm
<b>C</b>	<b>Col de cygne</b> Distance between spindle and column Distancia entre columna y broca Distância entre o encaixe e a base	162,5 mm
<b>D</b>	<b>ø de la colonne</b> Column diameter Ø de la columna Diâmetro da coluna	ø 72 mm
<b>E</b>	<b>ø maxi de perçage en cône morse (CM)</b> Maximum ø drilling with morse taper (MT) Ø max. de broca en cono morse Capacidade máxima de perfuração com encaixe	ø 22 mm
<b>F</b>		420/610 mm
	<b>Dimensions de la table</b> Table sizes Dimensiones de la mesa Dimensão da mesa	ø 290 mm
	<b>Table ajustable par crémaillère</b> Adjustable table with toothed rack Mesa ajustable por cremallera Dimensões da mesa	✓
	<b>Visée laser</b> Laser target Visor láser Laiser	✓
	<b>Largeur des mâchoires de l'étau</b> Jaws width Anchura de las mordazas Largura das Garras	100 mm N°4
	<b>Dimensions hors tout</b> Overall sizes Altura total Dimensões	860x260x265 mm 50,90 kg
	Master Box	
	Qty / Pallet	
	Qty / ctr 20 ft	
		895x490x300 mm 1 x 56,00 kg 7 pcs 320 pcs

